


June 2004



Features


- Optimized wavelength for Plastic optical fiber
- High Bandwidth
- No threshold
- Surface emitting
- High coupling efficiency
- Hermetically sealed

Applications

- Fast Ethernet
- IEEE1394b
- 155 Mbps ATM
- Home networking
- Industrial applications

Ordering Information

ZL60003/TBD TO-46 Package

-20°C to +70°C**Figure 1 - Pin Description**

Description

This unique Resonant Cavity Surface-Emitting LED (RCLED) is designed for optical communications over Plastic Optical Fiber (POF) in applications such as Fast Ethernet, IEEE1394b (S100, S200) and 155 Mbps ATM. Optimised high-speed performance can be achieved by use of a suitable electrical pre-emphasis within the drive circuitry.

ZL60003 is also well suited for applications where visible light is required, such as in sensing and positioning.

Optical and Electronic characteristics (25°C Case temperature)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Fiber-Coupled Power	P_{fiber}	1.2			mW	$I_F = 30 \text{ mA}$ (Note1)
Optical Power	P_o		2.0		mW	$I_F = 30 \text{ mA}$
Beam Divergence (FWHM)	$2\theta_{1/2}$		25		deg	$I_F = 30 \text{ mA}$
Rise and Fall Time	t_R, t_F			3.5	ns	$I_F = 30 \text{ mA}$ (Note1,2)
Peak Wavelength	λ_p	640	650	660	nm	$I_F = 30 \text{ mA}$ (Note1)
Spectral Width (FWHM)	$\Delta\lambda$			20	nm	$I_F = 30 \text{ mA}$ (Note1)
Forward Voltage	V_F			2.3	V	$I_F = 30 \text{ mA}$

Note 1: Fiber: POF 980/1000 μm Step Index, NA=0.48. For high speed communication, a low NA POF or a graded index POF are recommended.

Note 2: Unfiltered 20%-80% measurement. Note significant improvements can be achieved by use of pre-emphasis in the drive circuitry.


Absolute Maximum Ratings

Parameter	Symbol	Limit
Storage Temperature	T_{stg}	-55 to +125°C
Operating Temperature	T_{op}	-20 to +70°C
Electrical Power Dissipation	P_{tot}	130 mW
Continuous Forward Current ($f < 10 \text{ kHz}$)	I_F	40 mA
Peak Forward Current (duty cycle < 50%, $f > 1 \text{ MHz}$)	I_{FRM}	85 mA
Reverse Voltage	V_R	5 V
Soldering Temperature (2 mm from the case for 10 sec.)	T_{sld}	260°C


Thermal Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit
Thermal Resistance - Infinite Heat Sink	R_{thjc}		200		°C/W
Thermal Resistance - No Heat Sink	R_{thja}		500		°C/W
Temp. Coefficient - Wavelength	$d\lambda/dT_j$		0.08		nm/°C
Optical Power - Fiber Coupled	dP_f/dT_j		-0.7		%/°C

BOTTOM VIEW (10 : 1)



SIDE VIEW



NOTES:-

1. All dimensions in mm.
2. General tol. ISO-2768-mK.
3. Coating: Case: Ni 1,5-2,5 μm .
Header: Ni 2-3 μm / Au min 1,32 μm .

© Zarlink Semiconductor 2002. All rights reserved.

ISSUE	1			
ACN	JS004076R1A			
DATE	22-MAR-03			
APPRD.	TD/BE			



	Package code TB
Previous package codes	Drawing type Package drawing, TO-46 with lens
	Title JS004076



**For more information about all Zarlink products
visit our Web Site at
www.zarlink.com**

Information relating to products and services furnished herein by Zarlink Semiconductor Inc. or its subsidiaries (collectively "Zarlink") is believed to be reliable. However, Zarlink assumes no liability for errors that may appear in this publication, or for liability otherwise arising from the application or use of any such information, product or service or for any infringement of patents or other intellectual property rights owned by third parties which may result from such application or use. Neither the supply of such information or purchase of product or service conveys any license, either express or implied, under patents or other intellectual property rights owned by Zarlink or licensed from third parties by Zarlink, whatsoever. Purchasers of products are also hereby notified that the use of product in certain ways or in combination with Zarlink, or non-Zarlink furnished goods or services may infringe patents or other intellectual property rights owned by Zarlink.

This publication is issued to provide information only and (unless agreed by Zarlink in writing) may not be used, applied or reproduced for any purpose nor form part of any order or contract nor to be regarded as a representation relating to the products or services concerned. The products, their specifications, services and other information appearing in this publication are subject to change by Zarlink without notice. No warranty or guarantee express or implied is made regarding the capability, performance or suitability of any product or service. Information concerning possible methods of use is provided as a guide only and does not constitute any guarantee that such methods of use will be satisfactory in a specific piece of equipment. It is the user's responsibility to fully determine the performance and suitability of any equipment using such information and to ensure that any publication or data used is up to date and has not been superseded. Manufacturing does not necessarily include testing of all functions or parameters. These products are not suitable for use in any medical products whose failure to perform may result in significant injury or death to the user. All products and materials are sold and services provided subject to Zarlink's conditions of sale which are available on request.

Purchase of Zarlink's I²C components conveys a licence under the Philips I²C Patent rights to use these components in and I²C System, provided that the system conforms to the I²C Standard Specification as defined by Philips.

Zarlink, ZL and the Zarlink Semiconductor logo are trademarks of Zarlink Semiconductor Inc.

Copyright Zarlink Semiconductor Inc. All Rights Reserved.

TECHNICAL DOCUMENTATION - NOT FOR RESALE
